BLITZ Tap Range Blitz Bath Filler Chrome



	Specification	
	Style:	Contemporary
	Product Type:	Taps
	Finish/Colour:	Chrome
	Main Construction Material:	Brass
	Mount Type:	Deck Mounted
	Handle Type:	Lever
	Connection Inlet:	3/4" BSP
	Connection Outlet:	N/A
	Number of Tap Holes:	2
	Valve/Cartridge Type:	3/4" Ceramic Disc Valves
	Plumbing System Requirements:	All
Features:	Working Pressure Range:	Min 0.2 Bar, Max 5.0 Bar
Metal Backnuts	Maximum Hot Water Temperature: °C	65
 Ceramic Disc 3/4" valve 	Maximum Dynamic Pressure: (bar)	5
	Maximum Static Pressure: (bar)	10
	Flow Type:	Single
	Flow Rate: (I/min @ 3 bar)	55
	Isolation Included:	No
Product Certifications:	Dimensions (m	
For more products, visit our website: http://www.bristan.com	System Pressure (bar) BTZ BF C - Single Outlet	ates (I/min) 0.2 0.5 1 2 3 5 14.3 22.6 31.8 44.9 55 71.1
TECHNICAL DATA SHEET	BTZ BF C - Mixed	24.6 38.1 53.8 76 93.1 120.3 BRISTAN TAPS & SHOWERS D3

Bristan, Birch Coppice Business Park, Dordon, Tamworth, B78 ISG. Telephone: 0844 701 6274. Facsimile: 0844 701 6275. Web Site: www.bristan.com Email: enquire@bristan.com. The information contained on this page was correct at date of issue. Fitting Dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. Bristan pursues a policy of continuing improvement in design and performance of its products and so reserves the right to change specifications without prior notice.