## COBALT SHWR PK

## COBALT Shower Range Complete Cobalt Recessed Dual Control

Shower Pack



Feati	ıres.

- **Dual control**
- Integral two outlet diverter
- Supplied with 200mm square shower rose, shower arm, wall outlet and a shower kit with single mode handset

Specification						
Style:	Contemporary					
Main Construction Material:	Brass					
No of Controls:	2					
Shower Type:	Recessed					
Shower Head Type:	Both					
Valve/Cartridge Type:	35mm Thermostatic Cartridge					
Maximum Hot Water Supply Temperature °C:	60					
Dynamic Pressure Range: (bar)	5					
Maximum Static Pressure: (bar)	10					
Plumbing System Suitability:	All - Ideally balanced					
Working Pressure Range:	Min. 0.2, Max. 5.0 Bar					
Flow Rate: (I/min @ 3 bar)	33					
Connection Inlet:	15mm Compression					
Isolation Valve Included:	No					
Check Valve Included:	No					

## **Product Certifications:**



For more products, visit our website: http://www.bristan.com



Dimensions (measurements in mm)							
200 170 200 113 150 (Centre)							
G1/2" (female)    G1/2" (male)							

Flow Rates (I/min)								
System Pressure (bar)	0.2	0.5	1	2	3	5		
Outlet 1	6.9	12.8	19	27.6	33.8	43.6		
Outlet 2	6.7	12.5	18.5	27	33	42.6		

TECHNICAL DATA

