# Mira Sport Thermostatic

Electric Shower Range

Consistent, safer showering with maximum performance - it's the reassurance of thermostatic temperature control.

# **Product Information**

Description	Colour	Product No.
Mira Sport Thermostatic 9.0kW	White/Chrome	1.1746.005
Mira Sport Thermostatic 9.8kW	White/Chrome	1.1746.006

## Features & Benefits

Temi	nera <sup>.</sup>	ture	cont	rol

Thermostatic temperature stability

## Easy to fit

Adjustable slide bar fits over holes left by previous shower kit

### Easy to service

Easy filter access

### For your customer

Separate flow and temperature controls

Push button on/off

Mira Sensi-flo $^{\text{TM}}$  helps prevent scalding

Mira Clearscale™ and Dual Element™ technology

reduces limescale by up to 50%

Phased shutdown flushes hot water from the tank making it

safe for the next user

4 spray 11cm showerhead with rub-clean nozzles







# **Product Specification**

### **Tech Details**

Temperature control

Control type: Thermostatic (SMA)

Installation

Power options: 9.0kW 240V AC (8.3kW 230V AC) 9.8kW 240v AC (9.0kW

230V AC)

Supply voltage:  $230v \pm 10\%$ 

Supply rating: 40 amp (9.0kW); 45 amp (9.8kW)

Terminal Block connections: Maximum 16mm2

Water entry points: Left (rising, falling & rear)

Cable entry points: Left (rising, falling & rear)

Inlet connections: Brass inlet connector. 15mm compression fitting

Outlet connections: 1/2" BSP Male

Supply Conditions

Minimum maintained pressure: 0.7 bar (7 metre head)

Maximum maintained pressure: 5.0 bar (50 metre head)

Maximum static pressure: 10.0 bar (100 metre head)

### Performance

Temperature stability: ± 2°C

### Safety Features

Phased shutdown: Yes

Factory set to safe max temp: Factory set at 48°C

Mira Sensi-flo™: Yes

#### Annrovals

Energy Efficiency: Class A

### **Dimensions**







