

# Single lever bathtub mixer for concealed installation # N15210018010

|< 170 mm >|



Single lever bathtub mixer for concealed installation	Dimension	Weight	Order number
Number of outlets: 2, Chrome, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Hand shower, Tub filler, Outlet/Diverter: Shut-off and diverter valve, Security combination, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Diameter escutcheon: 170 mm, Including functional unit, Including trim parts			
<b>Colors</b>			
10 Chrome			
<b>Variant</b>			
Consumer selection: Tub filler, Hand shower, Outlet/Diverter: Diverter valve, Flow rate (3 bar): 22,5 l/min	170x170 mm	2.150 kg	N15210018010
<b>Necessary accessory</b>			
Basic Set Shut-off valve: Yes	164 x 105 mm	1.4 kg	GK0900001
Basic Set Dimensions of water supply connection: DN 15, Shut-off valve: No	164 x 105 mm	1.24 kg	GK0900000

*All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in mm and are non-binding. Exact measurements, in particular for customised installation scenarios, can only be taken from the finished piece.*

**Single lever bathtub mixer for concealed installation #  
N15210018010**

| < 170 mm > |

