

Single lever bathtub mixer for exposed installation # N15230000010

|< 137 mm >|



Single lever bathtub mixer for exposed installation	Dimension	Weight	Order number
Chrome, Connection type for water supply connection: S-connections, Dimension of connection hose: 1/2", Centre distance: 150 mm ± 10 mm, Ceramic cartridge, recommended operating pressure: 1 - 5 bar, Spray mode: Normal spray, Diverter valve, Diverter automatically reverts from hand shower to bath spout when turned off			
Colors			
10 Chrome			
Variant			
Noise class: II	216x137 mm	1.300 kg	N15230000010
Suitable accessories			
Hand shower 1jet Spray mode: Rain, Dimensions of water supply connection: 1/2", Silicone nubs	245 x 110 mm	0.16 kg	UV0650013
Hand shower 1jet MinusFlow MinusFlow, Spray mode: Rain, Dimensions of water supply connection: 1/2", Flow rate (3 bar): 9 l/min, Silicone nubs	245 x 110 mm	0.16 kg	UV0652013
Hand shower 1jet Spray mode: Rain, Dimensions of water supply connection: 1/2", Silicone nubs	245 x 110 mm	0.16 kg	UV0650014
Hand shower 1jet MinusFlow MinusFlow, Spray mode: Rain, Dimensions of water supply connection: 1/2", Flow rate (3 bar): 9 l/min, Silicone nubs	245 x 110 mm	0.16 kg	UV0652014
Hand shower 3jet Spray mode: SoftRain, Rain, IntenseRain, Dimensions of water supply connection: 1/2", Spray mode selection: Rotating blasting disc, Silicone nubs	245 x 110 mm	0.2 kg	UV0650015
Hand shower 3jet MinusFlow MinusFlow, Spray mode: SoftRain, Rain, IntenseRain, Dimensions of water supply connection: 1/2", Spray mode selection: Rotating blasting disc, Flow rate (3 bar): 9 l/min, Silicone nubs	245 x 110 mm	0.2 kg	UV0652015
Hand shower 3jet Spray mode: SoftRain, Rain, IntenseRain, Dimensions of water supply connection: 1/2", Spray mode selection: Rotating blasting disc, Silicone nubs	245 x 110 mm	0.2 kg	UV0650016

Single lever bathtub mixer for exposed installation # N15230000010

|< 137 mm >|

Hand shower 3jet MinusFlow MinusFlow, Spray mode: SoftRain, Rain, IntenseRain, Dimensions of water supply connection: 1/2", Spray mode selection: Rotating blasting disc, Flow rate (3 bar): 9 l/min, Silicone nubs	245 x 110 mm	0.2 kg	UV0652016
Hand shower 3jet Click! Spray mode: Rain, Pulse, Mono, Dimensions of water supply connection: 1/2", Spray mode selection: Push button, Silicone nubs	240 x 120 mm	0.24 kg	UV0650017
Hand shower 3jet Click! MinusFlow MinusFlow, Spray mode: Rain, Pulse, Mono, Dimensions of water supply connection: 1/2", Spray mode selection: Push button, Flow rate (3 bar): 9 l/min, Silicone nubs	240 x 120 mm	0.24 kg	UV0652017
Stick hand shower 1jet Dimensions of water supply connection: 1/2", Silicone nubs	187 x 25 mm	0.14 kg	UV0640001
Stick hand shower MinusFlow, Rain, Flow rate (3 bar): 9 l/min, Silicone nubs	187 x 25 mm	0.14 kg	UV0642001
Stick hand shower 1jet Dimensions of water supply connection: 1/2", Silicone nubs	212 x 22 mm	0.18 kg	UV0640002
Stick hand shower MinusFlow, Flow rate (3 bar): 9 l/min, Silicone nubs	212 x 22 mm	0.18 kg	UV0642002
Hand shower holder Material: ABS, Hand shower holder: Fixed, Mounting bracket shape: Conical	38 x 58 mm	0.04 kg	UV0620001
Shower hose Rotation lock: Yes, Dimensions of water supply connection: 1/2", Nut shape: Conical, 1250 mm	1250 x 23 mm	0.28 kg	UV0610006
Shower hose Rotation lock: Yes, Dimensions of water supply connection: 1/2", Nut shape: Conical, 1600 mm	1600 x 23 mm	0.34 kg	UV0610007
Shower hose Rotation lock: Yes, Dimensions of water supply connection: 1/2", Nut shape: Conical, 1800 mm	1800 x 23 mm	0.37 kg	UV0610008
Hand shower holder Material: Brass, Hand shower holder: Fixed, Escutcheon shape: Round, Mounting bracket shape: Conical	55 x 102 mm	0.3 kg	UV0620007
Hand shower holder Material: Brass, Hand shower holder: Fixed, Escutcheon shape: Square, Mounting bracket shape: Conical	55 x 102 mm	0.3 kg	UV0620026

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in mm and are non-binding. Exact measurements, in particular for customised installation scenarios, can only be taken from the finished piece.

