

**Shower rail 900** # UV06000040.. / UV06000040.. /  
UV06000040.. / UV06000040.. / UV06000040..

|< 70 mm >|



Shower rail 900	Dimension	Weight	Order number
100 mm, Hand shower holder: height adjustable			
<b>Colors</b>			
04 Brushed Bronze 10 Chrome 34 Polished Gold 46 Black Matt 70 Brushed Stainless Steel			
<b>Variant</b>			
mm, Bronze Brushed	900x70 mm	0.385 kg	UV06000040..
mm, Chrome	900x100 mm	0.360 kg	UV06000040..
mm, Gold Polished	900x70 mm	0.385 kg	UV06000040..
mm, Black Matt	900x100 mm	0.360 kg	UV06000040..
mm, Stainless steel Brushed	900x70 mm	0.385 kg	UV06000040..
<b>Suitable accessories</b>			
Hand shower 3jet Click! MinusFlow MinusFlow, Spray mode: Rain, Pulse, Mono, Spray mode selection: Push button, Flow rate 240 x 120 mm (3 bar): 9 l/min, Silicone nubs		0.24 kg	UV0652017
Stick hand shower MinusFlow, Rain, Flow rate (3 bar): 9 l/min, Silicone nubs	187 x 25 mm	0.14 kg	UV0642001
Single lever shower mixer for exposed installation Water connection: S-connections, 1/2", Ceramic cartridge, recommended operating pressure: 1 - 5 bar, Non-return valve in the hose connection	216 x 165 mm	1.66 kg	WA4230000
Thermostatic shower mixer for exposed installation 1000 Water connection: 1/2", Thermostat cartridge, recommended operating pressure: 1 - 5 bar, Safety lock at 38 °C, Non-return valve in the hose connection	303 x 113 mm	2.25 kg	TH4220000
<b>Suitable accessories for mm, Chrome</b>			

## Shower rail 900 # UV06000040.. / UV06000040.. / UV06000040.. / UV06000040.. / UV06000040..

|< 70 mm >|

Single lever shower mixer for exposed installation Chrome, Water connection: 1/2", Ceramic cartridge, recommended operating pressure: 1 - 5 bar, Non-return valve in the hose connection, Noise class: II	209 x 133 mm	1.5 kg	B14230000
Thermostatic shower mixer for exposed installation Chrome, Water connection: 1/2", Thermostat cartridge, recommended operating pressure: 1 - 5 bar, Safety lock at 38 °C, Diverter valve, Non-return valve in the hose connection, Noise class: II	260 x 118 mm	1.8 kg	B14220000
Single lever shower mixer for concealed installation Number of outlets: 1, Chrome, Ceramic cartridge, Number of outlets: 1, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Diameter escutcheon: 170 mm, Including functional unit, Including trim parts	170 x 86 mm	1.8 kg	B14210010
Single lever shower mixer for concealed installation Number of outlets: 1, Chrome, Ceramic cartridge, Number of outlets: 1, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Diameter escutcheon: 170 mm, Including functional unit, Including trim parts	170 x 87 mm	1.75 kg	B24210010
Single lever shower mixer for exposed installation Chrome, Ceramic cartridge, recommended operating pressure: 1 - 5 bar, Non-return valve in the hose connection, Noise class: II	179 x 137 mm	1.3 kg	B24230000
Thermostatic shower mixer for exposed installation Chrome, Thermostat cartridge, recommended operating pressure: 1 - 5 bar, Safety lock at 38 °C, Diverter valve, Non-return valve in the hose connection, Noise class: II	260 x 113.5 mm	1.8 kg	B24220000
Single lever shower mixer for exposed installation Chrome, Water connection: 1/2", Ceramic cartridge, recommended operating pressure: 3 - 5 bar, Non-return valve in the hose connection, Flow rate (3 bar): 18,5 l/min	209 x 140 mm	1.17 kg	DE4230000
Single lever shower mixer for concealed installation Number of outlets: 1, Chrome, Ceramic cartridge, Number of outlets: 1, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Diameter escutcheon: 170 mm, Including functional unit, Including trim parts	170 x 80 mm	1.8 kg	DE4210010
Single lever shower mixer for concealed installation Number of outlets: 1, Chrome, Water connection: Basic Set, Ceramic cartridge, Number of outlets: 1, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Diameter escutcheon: 170 mm, Including functional unit, Including trim parts	170 x 97 mm	1.8 kg	WT4210010
Single lever shower mixer for exposed installation Chrome, Water connection: S-connections, 1/2", Centre distance: 150 mm ± 10 mm, Ceramic cartridge, recommended operating pressure: 1 - 5 bar	215 x 128 mm	0.9 kg	N14230000
Single lever mixer concealed set Number of outlets: 1, Chrome, Water connection: Basic Set, Ceramic cartridge, Number of outlets: 1, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Including functional unit, Including trim parts	115 x 83 mm	0.7 kg	N14210007
Hand shower 1jet Spray mode: Rain, Silicone nubs	245 x 110 mm	0.16 kg	UV0650014
Hand shower 1jet MinusFlow MinusFlow, Spray mode: Rain, Flow rate (3 bar): 9 l/min, Silicone nubs	245 x 110 mm	0.16 kg	UV0652014
Hand shower 3jet Spray mode: SoftRain, Rain, IntenseRain, Spray mode selection: Rotating blasting disc, Silicone nubs	245 x 110 mm	0.2 kg	UV0650016

## Shower rail 900 # UV06000040.. / UV06000040.. / UV06000040.. / UV06000040.. / UV06000040..

|< 70 mm >|

Single lever shower mixer for exposed installation Water connection: 1/2", Ceramic cartridge, recommended operating pressure: 1 - 5 bar, Non-return valve in the hose connection	255 x 106 mm	1.68 kg	CE4230000
Single lever mixer concealed set Number of outlets: 1, Water connection: Basic Set, Ceramic cartridge, Number of outlets: 1, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round	125 x 72 mm	1.1 kg	CE4210007
Single lever mixer concealed set Number of outlets: 1, Water connection: Basic Set, Ceramic cartridge, Number of outlets: 1, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Including functional unit, Including trim parts	125 x 88 mm	1.17 kg	WA4210007
Single lever mixer concealed set Number of outlets: 1, Water connection: Basic Set, Ceramic cartridge, Number of outlets: 1, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Square, 130x130 mm, Including functional unit, Including trim parts	130 x 76 mm	1.08 kg	MH4210007
Single lever shower mixer for concealed installation Number of outlets: 1, Chrome, Water connection: Basic Set, Ceramic cartridge, Number of outlets: 1, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Diameter escutcheon: 170 mm, Including functional unit, Including trim parts	170 x 86 mm	1.75 kg	N14210010
Single lever shower mixer for concealed installation Number of outlets: 1, Water connection: Basic Set, Ceramic cartridge, Number of outlets: 1, recommended operating pressure: 1 - 5 bar, Flow rate (3 bar): 24,5 l/min, Escutcheon shape: Round	170 x 82 mm	1.66 kg	CE4210010
<b>Suitable accessories for mm, Chrome, mm, Black Matt</b>			
Single lever shower mixer for exposed installation Ceramic cartridge, recommended operating pressure: 1 - 5 bar, Flow rate (3 bar): 12,6 l/min, Noise class: II	272 x 103 mm	1.69 kg	C14230000
Single lever shower mixer for concealed installation Number of outlets: 1, Ceramic cartridge, Number of outlets: 1, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Square, Including functional unit, Including trim parts	150 x 77 mm	1.63 kg	C14210009
Single lever shower mixer for concealed installation Number of outlets: 1, Water connection: Basic Set, Ceramic cartridge, Number of outlets: 1, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Diameter escutcheon: 170 mm, Including functional unit, Including trim parts	170 x 77 mm	1.66 kg	C14210010
Single lever shower mixer for exposed installation Ceramic cartridge, recommended operating pressure: 1 - 5 bar, Non-return valve in the hose connection	280 x 113 mm	3.4 kg	TU4230000
Single lever shower mixer for concealed installation Number of outlets: 1, Ceramic cartridge, Number of outlets: 1, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Including functional unit, Including trim parts	170 x 86 mm	1.8 kg	TU4210010
Hand shower 1jet Spray mode: Rain, Silicone nubs	245 x 110 mm	0.16 kg	UV0650013
Hand shower 1jet MinusFlow MinusFlow, Spray mode: Rain, Flow rate (3 bar): 9 l/min, Silicone nubs	245 x 110 mm	0.16 kg	UV0652013
Hand shower 3jet Spray mode: SoftRain, Rain, IntenseRain, Spray mode selection: Rotating blasting disc, Silicone nubs	245 x 110 mm	0.2 kg	UV0650015

**Shower rail 900 # UV06000040.. / UV06000040.. /  
UV06000040.. / UV06000040.. / UV06000040..**

|< 70 mm >|

Hand shower 3jet MinusFlow MinusFlow, Spray mode: SoftRain, Rain, IntenseRain, Spray mode selection: Rotating blasting disc, Flow rate (3 bar): 9 l/min, Silicone nubs	245 x 110 mm	0.2 kg	UV0652015
Hand shower 3jet Click! Spray mode: Rain, Pulse, Mono, Spray mode selection: Push button, Silicone nubs	240 x 120 mm	0.24 kg	UV0650017
Stick hand shower 1jet Silicone nubs	187 x 25 mm	0.14 kg	UV0640001
Stick hand shower 1jet Silicone nubs	212 x 22 mm	0.18 kg	UV0640002
Stick hand shower MinusFlow, Flow rate (3 bar): 9 l/min, Silicone nubs	212 x 22 mm	0.18 kg	UV0642002
Single lever shower mixer for exposed installation Water connection: 1/2", Ceramic cartridge, recommended operating pressure: 1 - 5 bar	255 x 105 mm	2.07 kg	MH4230000
Single lever shower mixer for concealed installation Number of outlets: 1, Water connection: Basic Set, Ceramic cartridge, Number of outlets: 1, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Square, Including functional unit, Including trim parts	150 x 82 mm	1.75 kg	MH4210010
Single lever shower mixer for concealed installation Number of outlets: 1, Water connection: Basic Set, Ceramic cartridge, Number of outlets: 1, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Including functional unit, Including trim parts	170 x 92 mm	1.8 kg	WA4210010
<b>Suitable accessories for mm, Chrome, mm, Stainless steel Brushed, mm, Gold Polished, mm, Bronze Brushed</b>			
Hand shower 3jet MinusFlow MinusFlow, Spray mode: SoftRain, Rain, IntenseRain, Spray mode selection: Rotating blasting disc, Flow rate (3 bar): 9 l/min, Silicone nubs	245 x 110 mm	0.2 kg	UV0652016
Shower rail 800 Hand shower holder: height adjustable	810 x 60 mm	0.8 kg	UV0600005
Shower rail 900 100 mm, Hand shower holder: height adjustable	900 x 100 mm	0.385 kg	UV0600004
Shower rail 700 mm, Hand shower holder: height adjustable	700 x 70 mm	0.32 kg	UV0600003

*All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in mm and are non-binding. Exact measurements, in particular for customised installation scenarios, can only be taken from the finished piece.*

