

**Single lever shower mixer for exposed installation #**  
 WA42300000.. / WA42300000.. / WA42300000.. / WA42300000..  
 / WA42300000..

|< 113 mm >|



Single lever shower mixer for exposed installation	Dimension	Weight	Order number
Connection type for water supply connection: S-connections, Dimension of connection hose: 1/2", Ceramic cartridge, recommended operating pressure: 1 - 5 bar, Non-return valve in the hose connection			
<b>Colors</b>			
04 Brushed Bronze 10 Chrome 34 Polished Gold 46 Black Matt 70 Brushed Stainless Steel			
<b>Variant</b>			
Bronze Brushed, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 24 l/min, Noise class: II	216x113 mm	1.660 kg	WA42300000..
Chrome, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 24 l/min, Noise class: II	216x113 mm	1.660 kg	WA42300000..
Gold Polished, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 24 l/min, Noise class: II	216x113 mm	1.660 kg	WA42300000..
Black Matt, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 24 l/min, Noise class: II	216x113 mm	1.660 kg	WA42300000..
Stainless steel Brushed, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 24 l/min, Noise class: II	216x113 mm	1.660 kg	WA42300000..
<b>Suitable accessories</b>			
Hand shower 3jet Click! MinusFlow MinusFlow, Spray mode: Rain, Pulse, Mono, Dimensions of water supply connection: 1/2", Spray mode selection: Push button, Flow rate (3 bar): 9 l/min, Silicone nubs	240 x 120 mm	0.24 kg	UV0652017
Shower rail 900 100 mm, Hand shower holder: height adjustable	900 x 70 mm	0.36 kg	UV0600004
Shower hose Rotation lock: Yes, Dimensions of water supply connection: 1/2", Nut shape: Conical, 1600 mm	1600 x 23 mm	0.34 kg	UV0610007

**Single lever shower mixer for exposed installation #**  
 WA42300000.. / WA42300000.. / WA42300000.. / WA42300000..  
 / WA42300000..

|< 113 mm >|

<b>Suitable accessories for Bronze Brushed, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 24 l/min, Noise class: II, Chrome, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 24 l/min, Noise class: II, Gold Polished, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 24 l/min, Noise class: II, Stainless steel Brushed, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 24 l/min, Noise class: II</b>			
Hand shower 3jet MinusFlow MinusFlow, Spray mode: SoftRain, Rain, IntenseRain, Dimensions of water supply connection: 1/2", Spray mode selection: Rotating blasting disc, Flow rate (3 bar): 9 l/min, Silicone nubs	245 x 110 mm	0.2 kg	UV0652016
Hand shower 1jet Spray mode: Rain, Dimensions of water supply connection: 1/2", Silicone nubs	245 x 110 mm	0.16 kg	UV0650014
Hand shower 1jet MinusFlow MinusFlow, Spray mode: Rain, Dimensions of water supply connection: 1/2", Flow rate (3 bar): 9 l/min, Silicone nubs	245 x 110 mm	0.16 kg	UV0652014
Hand shower 3jet Spray mode: SoftRain, Rain, IntenseRain, Dimensions of water supply connection: 1/2", Spray mode selection: Rotating blasting disc, Silicone nubs	245 x 110 mm	0.2 kg	UV0650016
<b>Suitable accessories for Chrome, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 24 l/min, Noise class: II, Black Matt, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 24 l/min, Noise class: II</b>			
Hand shower 1jet Spray mode: Rain, Dimensions of water supply connection: 1/2", Silicone nubs	245 x 110 mm	0.16 kg	UV0650013
Hand shower 1jet MinusFlow MinusFlow, Spray mode: Rain, Dimensions of water supply connection: 1/2", Flow rate (3 bar): 9 l/min, Silicone nubs	245 x 110 mm	0.16 kg	UV0652013
Hand shower 3jet Spray mode: SoftRain, Rain, IntenseRain, Dimensions of water supply connection: 1/2", Spray mode selection: Rotating blasting disc, Silicone nubs	245 x 110 mm	0.2 kg	UV0650015
Hand shower 3jet MinusFlow MinusFlow, Spray mode: SoftRain, Rain, IntenseRain, Dimensions of water supply connection: 1/2", Spray mode selection: Rotating blasting disc, Flow rate (3 bar): 9 l/min, Silicone nubs	245 x 110 mm	0.2 kg	UV0652015
Hand shower 3jet Click! Spray mode: Rain, Pulse, Mono, Dimensions of water supply connection: 1/2", Spray mode selection: Push button, Silicone nubs	240 x 120 mm	0.24 kg	UV0650017
Shower rail 700 mm, Hand shower holder: height adjustable	700 x 70 mm	0.32 kg	UV0600003
Shower hose Rotation lock: Yes, Dimensions of water supply connection: 1/2", Nut shape: Conical, 1250 mm	1250 x 23 mm	0.28 kg	UV0610006
Shower hose Rotation lock: Yes, Dimensions of water supply connection: 1/2", Nut shape: Conical, 1800 mm	1800 x 23 mm	0.37 kg	UV0610008
Shower rail 800 Hand shower holder: height adjustable	810 x 60 mm	1 kg	UV0600005

*All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in mm and are non-binding. Exact measurements, in particular for customised installation scenarios, can only be taken from the finished piece.*

Single lever shower mixer for exposed installation #  
 WA42300000.. / WA42300000.. / WA42300000.. / WA42300000..  
 / WA42300000..

|< 113 mm >|

