

Thermostatic concealed installation set # TH42000080.. / TH42000080.. / TH42000080.. / TH42000080..

|< 170 mm >|



Thermostatic concealed installation set	Dimension	Weight	Order number
Number of outlets: 2, Water connection: Basic Set, Thermostat cartridge, Safety lock at 38 °C, Outlet/Diverter: Shut-off and diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Flow rate (3 bar): 24 l/min, Escutcheon shape: Round, Including functional unit, Including trim parts			
Colors			
04 Brushed Bronze 10 Chrome 34 Polished Gold 46 Black Matt 70 Brushed Stainless Steel			
Variant			
Bronze Brushed	170x170 mm	2.320 kg	TH42000080..
Chrome	170x170 mm	2.320 kg	TH42000080..
Gold Polished	170x170 mm	2.320 kg	TH42000080..
Black Matt	170x170 mm	2.320 kg	TH42000080..
Stainless steel Brushed	170x170 mm	2.320 kg	TH42000080..

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in mm and are non-binding. Exact measurements, in particular for customised installation scenarios, can only be taken from the finished piece.

Thermostatic concealed installation set # TH42000080.. /
TH42000080.. / TH42000080.. / TH42000080..

| < 170 mm > |

