

**Thermostatic shower mixer for exposed installation 1000 #**  
**TH42200000.. / TH42200000.. / TH42200000.. / TH42200000.. /**  
**TH42200000..**

|< 65 mm >|



| Thermostatic shower mixer for exposed installation 1000  | Dimension    | Weight   | Order number |
|--|--------------|----------|--------------|
| Water connection: 1/2", Thermostat cartridge, recommended operating pressure: 1 - 5 bar, Safety lock at 38 °C, Non-return valve in the hose connection         |              |          |              |
| <b>Colors</b>  |              |          |              |
| 04 Brushed Bronze 10 Chrome 34 Polished Gold 46 Black Matt<br>70 Brushed Stainless Steel   |              |          |              |
| <b>Variant</b>   |              |          |              |
| Bronze Brushed, Water connection: S-connections, 1/2", Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 24,5 l/min, Noise class: II                         | 303x65 mm    | 2.250 kg | TH42200000.. |
| Chrome, Water connection: S-connections, 1/2", Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 24,5 l/min, Noise class: II                                 | 303x65 mm    | 2.250 kg | TH42200000.. |
| Gold Polished, Water connection: S-connections, 1/2", Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 24,5 l/min, Noise class: II                          | 303x65 mm    | 2.250 kg | TH42200000.. |
| Black Matt, Water connection: S-connections, 1/2", Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 24,5 l/min, Noise class: II                             | 303x65 mm    | 2.250 kg | TH42200000.. |
| Stainless steel Brushed, Water connection: S-connections, 1/2", Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 24,5 l/min, Noise class: II                | 303x65 mm    | 2.250 kg | TH42200000.. |
| <b>Suitable accessories</b>  |              |          |              |
| Hand shower 3jet Click! MinusFlow MinusFlow, Spray mode: Rain, Pulse, Mono, Spray mode selection: Push button, Flow rate (3 bar): 9 l/min, Silicone nubs       | 240 x 120 mm | 0.24 kg  | UV0652017    |
| Shower rail 900 100 mm, Hand shower holder: height adjustable  | 900 x 100 mm | 0.385 kg | UV0600004    |
| Shower hose Rotation lock: Yes, Nut shape: Conical, 1600 mm  | 1600 x 23 mm | 0.34 kg  | UV0610007    |
| <b>Suitable accessories for Chrome, Water connection: S-connections, 1/2", Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 24,5 l/min, Noise class: II</b> |              |          |              |
| Hand shower 1jet Spray mode: Rain, Silicone nubs   | 245 x 110 mm | 0.16 kg  | UV0650014    |
| Hand shower 1jet MinusFlow MinusFlow, Spray mode: Rain, Flow rate (3 bar): 9 l/min, Silicone nubs  | 245 x 110 mm | 0.16 kg  | UV0652014    |

**Thermostatic shower mixer for exposed installation 1000 #**  
**TH42200000.. / TH42200000.. / TH42200000.. / TH42200000.. /**  
**TH42200000..**

| < 65 mm > |

|  |              |         |           |
|--|--------------|---------|-----------|
| Hand shower 3jet Spray mode: SoftRain, Rain, IntenseRain, Spray mode selection: Rotating blasting disc, Silicone nubs  | 245 x 110 mm | 0.2 kg  | UV0650016 |
| <b>Suitable accessories for Chrome, Water connection: S-connections, 1/2", Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 24,5 l/min, Noise class: II, Black Matt, Water connection: S-connections, 1/2", Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 24,5 l/min, Noise class: II</b>   |              |         |           |
| Hand shower 1jet Spray mode: Rain, Silicone nubs   | 245 x 110 mm | 0.16 kg | UV0650013 |
| Hand shower 1jet MinusFlow MinusFlow, Spray mode: Rain, Flow rate (3 bar): 9 l/min, Silicone nubs  | 245 x 110 mm | 0.16 kg | UV0652013 |
| Hand shower 3jet Spray mode: SoftRain, Rain, IntenseRain, Spray mode selection: Rotating blasting disc, Silicone nubs  | 245 x 110 mm | 0.2 kg  | UV0650015 |
| Hand shower 3jet MinusFlow MinusFlow, Spray mode: SoftRain, Rain, IntenseRain, Spray mode selection: Rotating blasting disc, Flow rate (3 bar): 9 l/min, Silicone nubs   | 245 x 110 mm | 0.2 kg  | UV0652015 |
| Hand shower 3jet Click! Spray mode: Rain, Pulse, Mono, Spray mode selection: Push button, Silicone nubs  | 240 x 120 mm | 0.24 kg | UV0650017 |
| Shower rail 700 mm, Hand shower holder: height adjustable  | 700 x 100 mm | 0.32 kg | UV0600003 |
| Shower hose Rotation lock: Yes, Nut shape: Conical, 1250 mm  | 1250 x 23 mm | 0.28 kg | UV0610006 |
| Shower hose Rotation lock: Yes, Nut shape: Conical, 1800 mm  | 1800 x 23 mm | 0.37 kg | UV0610008 |
| Shower rail 800 Hand shower holder: height adjustable  | 810 x 60 mm  | 1 kg    | UV0600005 |
| <b>Suitable accessories for Chrome, Water connection: S-connections, 1/2", Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 24,5 l/min, Noise class: II, Bronze Brushed, Water connection: S-connections, 1/2", Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 24,5 l/min, Noise class: II, Gold Polished, Water connection: S-connections, 1/2", Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 24,5 l/min, Noise class: II, Stainless steel Brushed, Water connection: S-connections, 1/2", Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 24,5 l/min, Noise class: II</b> |              |         |           |
| Hand shower 3jet MinusFlow MinusFlow, Spray mode: SoftRain, Rain, IntenseRain, Spray mode selection: Rotating blasting disc, Flow rate (3 bar): 9 l/min, Silicone nubs   | 245 x 110 mm | 0.2 kg  | UV0652016 |

*All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in mm and are non-binding. Exact measurements, in particular for customised installation scenarios, can only be taken from the finished piece.*

