
# Geberit Duofix element for wall-hung WC, 112 cm, with Alpha concealed cistern 12 cm, 5.8 / 3 litres, Alpha01 flush plate, round, Selnova wall-hung WC, Rimfree









# **APPLICATION PURPOSES**

- For metal and wood frame walls
- For installation in part- or room-height prewalls
- · For installation in room-height partition walls
- For floor constructions 0–20 cm

# **CHARACTERISTICS**

- 2025 range
- Statically self-supporting frame, protected against corrosion with powder coating
- Frame for wall-hung WCs with connection dimensions as per EN 33 and projection up to 62 cm
- · Alternative fastening point for wall anchors
- Foot plates made of plastic
- Foot plate depth suitable for installation in U-profiles UW 50
- · Galvanised leg supports protected against corrosion
- · Connection bend can be mounted without tools
- Geberit Alpha concealed cistern 12 cm fully insulated against condensation
- Cistern fulfils standard requirements in accordance with EN 14055, Class II
- · For front actuation, suitable for dual flush
- · Immediate post flush possible with factory setting
- Water supply connection on the rear or top centre

- Protection box for service opening, can be cut to length, protects against moisture and dirt
- With conduit pipe for feed pipe for Geberit AquaClean shower toilets and for connection cable
- · Fastening option for electrical connection
- · Washdown WC
- Wall-hung
- Rimless WC ceramic appliance featuring Rimfree flush technology
- Easy fastening with Easy Fast Fixing (type EFF3)
- Type 1, full flush volume 6 / 5 / 4 l, in accordance with EN 997
- Shrouded
- · WC seat made of Duroplast
- 4 I flush

range

Overlapping WC lid

#### **TECHNICAL DATA**

Flow pressure	0.1–10 bar
Operating temperature, water	25 °C
max.	
Flush volume, factory setting	5.8/31
Flush volume large, adjustment	4/4.5/6/7.51
range	
Flush volume small, adjustment	2-4

Button shape round
Product material Vitreous china
Fastening distance 18 cm
Odour extraction unit No

## **SCOPE OF DELIVERY**

- Water supply connection unit R 1/2", compatible with MasterFix and MeplaFix, with integrated angle stop valve and adapter ring
- Protection box for service opening
- 2 wall anchors
- 2 fixing brackets
- · Geberit Alpha01 flush plate for dual flush, round
- · Connection set for WC, ø 90 mm
- Connection bend 90° made of PE-HD, ø 90 mm
- Adaptor socket made of PE-HD, ø 90 / 110 mm
- Fastening and protection material
- Geberit Selnova Premium wall-hung WC set, washdown, shrouded, Rimfree, with WC seat

### **ACCESSORIES**

- Geberit Duofix fastening material for stud clearance 50–57.5 cm
- · Geberit Duofix set of foot fastener on rear wall
- Geberit set of support brackets for WC ceramic appliances with small contact surfaces



• Geberit sound insulation set for wall-hung WC

• Geberit Duofix set of foot extensions 20 cm length

New article available from 01.06.2025